

# NEO® 8000e

## Unrivaled Backup and Archive for the Enterprise



Besides its people, a company's data is one of its most valuable assets. Keeping that data securely protected has become complex and expensive as companies are faced with massive data growth, increasingly stringent regulatory requirements and distributed environments that can range from across-the-hall to across-the-globe. The NEO 8000e provides the reliability, data availability and manageability features needed to address the backup and archive needs of the most demanding enterprise data centers.

### Superior Cost of Ownership

Embedded connectivity capability ensures that your NEO 8000e not only fits seamlessly into virtually any environment but also adapts to any changes in that environment, protecting your initial library investment for the long-haul. Features such as integrated partitioning let you multi-task with your NEO 8000e library, allocating each partition to a separate back-up task or environment without requiring additional costly hardware. Consuming less power than other enterprise-class tape libraries, NEO 8000e improves energy efficiency by reducing cooling and power requirements. Designed for enterprise environments but delivering mid-range simplicity, NEO 8000e's simplified configuration and installation approach results in lower installation, maintenance and service costs, making NEO 8000e a wise storage investment.

### Intelligent Management

The NEO 8000e conveniently and intelligently manages the backup/archive process from anywhere in the world through a web-based remote management interface, reducing administrative costs and improving data availability. Features such as email alerts proactively identify potential issues with your backup/archive operation and provide diagnostic information used to isolate potential failures, reducing service costs and downtime associated with problem resolution.

### High Data Availability

Whether it's robotic failover, redundant hot-swap power, high-performance tape drive management or advanced diagnostics capabilities, NEO 8000e eliminates single points of failure that can result in costly downtime. Unlike other midrange and enterprise libraries, NEO 8000e provides redundant robotics in scaled environments, ensuring that you have access to your data in the event of a robotic failure. Designed to meet the reliability, availability and serviceability needs of backup and archive operations in high-performance, high duty cycle data center environments, NEO 8000e provides a robust, reliable platform that ensures your data is automatically safe and always available.

### Flexibility

NEO 8000e's innovative multi-module design lets you effortlessly customize your backup and archive solution as your data storage needs change. Starting with 100 cartridge slots and adding capacity in 80-slot increments lets you seamlessly add storage as you need it but does not require additional hardware or disruptive reconfiguration. Tape drive modules can also be added for increased performance capability. Once you've filled up your base NEO 8000e, simply add an additional NEO 8000e module for increased storage capacity and performance.

### Highlights

- Backup/archive up to 15PB of data
- Transfer data at speeds of up to 64.8TB/hr.
- Protect your investment with a scalable architecture
- Ensure data availability with redundancy features
- Improve your efficiency and increase reliability with intelligent remote management
- Reduce your cost of ownership with energy and space-saving features

## Specifications

Library Configuration	Base Configuration			Maximum Configuration			Scaled Configuration		
	LTO-7	LTO-6	LTO-5	LTO-7	LTO-6	LTO-5	LTO-7	LTO-6	LTO-5
Number of cartridge	100			500			1000		
Number of cartridge drawers	1			6			12		
Number of slots per drawer	80			80			8		
Number of fixed cartridge cells	20			20			40		
Number of mail slots	15			15			30		
Max. number of tape drives supported	12			12			24		
Drive types supported	LTO-5, LTO-6, LTO-7			LTO-5, LTO-6, LTO-7			LTO-5, LTO-6, LTO-7		
<b>Capacity</b>	<b>LTO-7</b>	<b>LTO-6</b>	<b>LTO-5</b>	<b>LTO-7</b>	<b>LTO-6</b>	<b>LTO-5</b>	<b>LTO-7</b>	<b>LTO-6</b>	<b>LTO-5</b>
Max. native capacity	600TB	250TB	150TB	5PB	1.3PB	750TB	6PB	2.5PB	1.5PB
Max. compressed capacity	1.5PB	625TB	300TB	7.5PB	3.1PB	1.5PB	15PB	6.3PB	3.0PB
<b>Performance</b>									
Max. native data transfer rate	13TB/hr.	7TB/hr.	6TB/hr.	13TB/hr.	7TB/hr.	6TB/hr.	26PB/hr.	14TB/hr.	12TB/hr.
Max. compressed data transfer rate	32.4TB/hr.	18TB/hr.	12TB/hr.	32.4TB/hr.	18TB/hr.	12TB/hr.	64.8 TB/hr.	35TB/hr.	24TB/hr.
<b>Interfaces</b>	8Gb FC	8Gb FC	8Gb FC	8Gb FC	8Gb FC	8Gb FC	8Gb FC	8Gb FC	8Gb FC
<b>Dimensions</b>	76" x 24" x 41.5" (193 x 61 x 105 cm)			76" x 24" x 41.5" (193 x 61 x 105 cm)			76" x 48" x 41.5" (193 x 122 x 105 cm)		
HxWxD	705 lb. (320 kg)			758 lb. (344 kg)			1,516 lb. (688 kg)		
Weigh									
<b>Reliability</b>	> 4,000,000 cycles								
MBCF (mean cycles between failures)	< 15 minutes								
MTTR (mean time to repair)									
<b>Operation</b>	< 20 seconds								
Mount time	< 20 seconds								
Dismount time	< 25 seconds								
Inventory time (80 cartridges)	< 5 minutes								
Inventory time (500 cartridges)									
<b>Environmental</b>	0°C to 50°C								
Operating Temperature	15% to 85%								
Operating Humidity	100-240 VAC								
Voltage	47-63 Hz								
Frequency	484 watts								
Power (min)	1653								
BTU/hr.									
<b>Agency Approvals</b>	NRTL (US & Canada), CE, TUV GS								
Safety	FCC-A, ICES, CE, VCCI, BSMI,								
Emissions	RoHS, WEE								
International compliance									
<b>Accessories Included</b>	US power cord, serial cable, documentation (SCSI terminator included with SCSI configurations)								
<b>Optional Accessories</b>	LTO-6 tape drives, LTO-5 tape drives, LTO-6 media, LTO-5 media, LTO cleaning cartridges, additional mailslot magazines, capacity increase modules, additional power supplies, multi-module robotics assembly, NEO 8000e rear door option kit								
<b>Standard Warranty</b>	The NEO 8000e is covered by a one-year OverlandCare limited hardware warranty including Next Business Day Onsite support and 24 x 7 telephone support. NEO 8000e systems are eligible for enhanced maintenance options to augment the standard limited warranty. Support coverage of all expansion modules must be purchased separately and run concurrently with the primary unit. For full details of all of our service programs, please contact your preferred authorized reseller or contact Overland-Tandberg directly at +1 (858) 571-5555.								

Sales and support for Overland-Tandberg products and solutions are available in over 90 countries.  
Contact us today at [sales@overlandstorage.com](mailto:sales@overlandstorage.com) or [sales@tandbergdata.com](mailto:sales@tandbergdata.com)

DS\_v2\_feb08\_2018

©2017 Sphere 3D. All trademarks and registered trademarks are the property of their respective owners. The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. Sphere 3D shall not be liable for technical or editorial errors or omissions contained herein.