

1st level header -

DATA SHEET

Helvetica Neue LT Std - 55 Roman - 25 pt
Sentence case (white on core blue background, or dark blue 100/45/0/37 on white)

2nd level header - Helvetica Neue LT Std - 45 Light - 19 pt Sentence case (white on core blue background or dark blue 100/45/0/37 on white)

Stock images can be used instead of the blue banner if text can be read when placed on top. Smaller images can be placed to cover the right side of the blue banner. Product images with transparent backgrounds can be placed so that they are on both the blue banner and the white space below.

3rd level header - Helvetica Neue LT Std 55 Roman 0/47/100/8 16 pt

4th level header - Helvetica Neue LT Std - 55 Roman 100/34/0/2 11 pt

Text - Arial - 90% black. 10 pt with 12 pt leading if sufficient room is available. 9pt. or 8.5pt. is acceptable. Do not use text smaller than 7 pt anywhere if not absolutely necessary.

Only capitalize proper names. Every reference of company should be trademarked in first instance. After that, it should not be trademarked. Numbers 1 - 9 should be written out in full, i.e. one, two, three, etc.

Bullets:

- Use bullets or check marks not arrows or other symbols
- ✓ Bullets and check marks are Arial - orange - 0/47/100/8

Charts

Use rectangular boxes to form chart.
Separation bars are 10% black.
Vertical separator lines are 50% black.
Header bar should be same colour as category text with white title.
Description text is 90% black.

Use Helvetica Neue LT Std 57 Condensed
Text size is 8 pt if sufficient room is available.
7.5 pt is acceptable. Do not use text smaller than 7 pt.

Do not capitalize the beginning letter of each word, use sentence case, (i.e. Number of power supplies, NOT Number Of Power Supplies)

NEO Agility server	
Software:	NEO Agility server software
Operating system:	Microsoft Windows Server 2012 R2 Essentials
Processor	Intel Xeon 6-core processor; 1.6GHz/2.4GHz
RAM:	32GB/64GB
System disk:	SATA or SAS
Disk cache:	6TB or 9.6TB
Network connections:	1GB Ethernet standard/10GB Ethernet standard
Connections to library:	SAS (NEOs T48); SAS or FC (NEOxl 80); FC (NEO 8000e)
Number of power supplies:	2 power supplies standard
Power:	700 watts, redundancy
Temperature:	0°C to 40°C
Humidity:	20 to 80%
Dimensions:	1u; W-17.2" (437mm) x H-1.7" (43mm) x D-25.6" (650mm) /23.5" (597mm)
Weight:	46 lbs.
Rack rails:	Included
Standard warranty:	1 year Silver NBD (hardware) 1 year telephone support (software)

60/26/0/0 20/6/0/0 100/45/0/37 100/68/0/12 100/34/0/2 86/8/0/0 0/47/100/8 33/0/96/0 90% BLK 50% BLK 10% BLK 100% White



Note:
Use of green should be limited to items requiring more emphasis.

Sales and support for Overland-Tandberg products and solutions are available in over 90 countries.
Contact us today at sales@overlandtandberg.com

©2019 Overland-Tandberg. All trademarks and registered trademarks are the property of their respective owners. The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. Overland-Tandberg shall not be liable for technical or editorial errors or omissions contained herein.

DS_apr26_2017